


MULTIFIT TYPE



SAE STANDARD CONNECTIONS

M14110R*

NPTF SWIVEL MALE 60° CONE SEAT - SAE J516/J514




| PART. REF. | HOSE BORE | | | THREAD | DIMENSIONS mm | | | | |
|---------------|-----------|------|------|-----------|---------------|------|------|---|----------------|
| | DN | inch | Size | | T | B | A | C | H ₂ |
| M14110-04-02R | 6 | 1/4" | - 04 | 1/8" - 27 | 3,0 | 41,9 | 10,0 | | 17 |
| M14110-04-04R | 6 | 1/4" | - 04 | 1/4" - 18 | 4,0 | 46,4 | 14,5 | | 17 |
| M14110-04-06R | 6 | 1/4" | - 04 | 3/8" - 18 | 7,0 | 46,4 | 14,5 | | 19 |
| M14110-06-04R | 10 | 3/8" | - 06 | 1/4" - 18 | 4,0 | 50,5 | 14,5 | | 22 |
| M14110-06-06R | 10 | 3/8" | - 06 | 3/8" - 18 | 7,0 | 50,5 | 14,5 | | 22 |
| M14110-06-08R | 10 | 3/8" | - 06 | 1/2" - 14 | 9,3 | 55,2 | 19,2 | | 24 |
| M14110-08-06R | 12 | 1/2" | - 08 | 3/8" - 18 | 7,0 | 51,5 | 14,5 | | 27 |
| M14110-08-08R | 12 | 1/2" | - 08 | 1/2" - 14 | 9,3 | 59,0 | 19,2 | | 27 |
| M14110-12-12R | 19 | 3/4" | - 12 | 3/4" - 14 | 16,0 | 57,9 | 19,2 | | 32 |
| M14110-16-16R | 25 | 1" | - 16 | 1" - 11,5 | 19,8 | 65,8 | 24,2 | | 38 |

* Not to be used as a live swivel

M22812

NPSM FEMALE 60° CONE - SAE J516/J514 (THRUST-WIRE NUT)



| PART. REF. | HOSE BORE | | | THREAD | DIMENSIONS mm | | | | |
|--------------|-----------|------|------|-----------|---------------|------|------|---|----------------|
| | DN | inch | Size | | T | B | A | C | H ₂ |
| M22812-04-04 | 6 | 1/4" | - 04 | 1/4" - 18 | 4,0 | 17,5 | 4,2 | | 19 |
| M22812-06-04 | 10 | 3/8" | - 06 | 1/4" - 18 | 4,0 | 18,0 | 4,2 | | 19 |
| M22812-06-06 | 10 | 3/8" | - 06 | 3/8" - 18 | 7,0 | 20,9 | 6,0 | | 22 |
| M22812-08-08 | 12 | 1/2" | - 08 | 1/2" - 14 | 9,3 | 22,8 | 6,5 | | 27 |
| M22812-12-12 | 19 | 3/4" | - 12 | 3/4" - 14 | 15,0 | 24,5 | 9,0 | | 32 |
| M22812-16-16 | 25 | 1" | - 16 | 1" - 11,5 | 19,8 | 27,3 | 10,5 | | 38 |

