



### M20842

45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)



### M20843

45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M20843-04-04	6	1/4"	- 04	1/4" -19	4,0	36,0	4,9	15,0		19
M20843-06-06	10	3/8"	- 06	3/8" -19	7,0	44,5	6,1	18,5		22
M20843-08-08	12	1/2"	- 08	1/2" -14	9,3	52,0	6,5	20,5		27
M20842-10-10	16	5/8"	- 10	5/8" -14	12,5	63,5	9,7	27,5		30
M20842-12-12	19	3/4"	- 12	3/4" -14	15,5	71,0	8,5	29,0		32
M20842-16-12	25	1"	- 16	3/4" -14	15,0	79,5	8,5	29,0		32
M20842-16-16	25	1"	- 16	1" -11	19,8	90,5	10,6	35,6		38
M20842-16-20	25	1"	- 16	1.1/4" - 11	26,0	93,0	10,5	38,0		50
M20842-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	101,5	10,5	39,0		50
M20842-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	118,5	12,5	40,5		60
M20842-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	106,5	10,5	42,0		50
M20842-24-24	38	1.1/2"	- 24	1.1/2" -11	32,0	118,0	12,5	45,0		60
M20842-32-32	51	2"	- 32	2" -11	42,0	134,0	16,1	47,0		70