




# MULTIFIT TYPE



## BS STANDARD CONNECTIONS

### M20882F


90° BSP O-RING FEMALE COMPACT ELBOW 60° CONE  
BS5200 / ISO 12151-6 (THRUST-WIRE NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>1</sub>
M20882-04-04F	6	1/4"	- 04	1/4" - 19	4,0	20,0	4,9	22,0	14	19
M20882-06-06F	10	3/8"	- 06	3/8" - 19	7,0	23,1	6,1	27,5	19	22
M20882-08-08F	12	1/2"	- 08	1/2" - 14	9,3	24,9	6,5	31,1	22	27
M20882-10-10F	16	5/8"	- 10	5/8" - 14	12,5	24,6	9,7	32,5	24	28
M20882-12-12F	19	3/4"	- 12	3/4" - 14	15,0	37,5	8,5	36,0	27	32
M20882-16-16F	25	1"	- 16	1" - 11	20,0	51,8	10,6	44,0	36	38

### M10610

BSP MALE FLAT SEAT



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H <sub>1</sub>	
M10610-04-04	6	1/4"	- 04	1/4" - 19	6,0	25,5	11,0		19	
M10610-06-06	10	3/8"	- 06	3/8" - 19	9,5	28,1	12,0		22	
M10610-06-08	10	3/8"	- 06	1/2" - 14	13,0	30,6	14,0		27	
M10610-08-08	12	1/2"	- 08	1/2" - 14	13,0	31,1	14,0		27	
M10610-12-12	19	3/4"	- 12	3/4" - 14	18,0	35,5	16,0		32	