




MULTIFIT TYPE



DIN STANDARD CONNECTIONS


M21542

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY
DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)



M21543

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY
DIN 20066 / ISO 12151-2 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size			T	mm	B	A	C	E
M21543-03-12	5	3/16"	-03	M 12x1,5	6	3,0	35,0	1,7	16,0		14
M21542-04-12	6	1/4"	-04	M 12x1,5	6	3,0	39,0	2,2	18,0		17
M21543-04-14	6	1/4"	-04	M 14x1,5	8	4,0	38,0	1,7	16,5		17
M21543-04-16	6	1/4"	-04	M 16x1,5	10	6,0	38,0	2,1	17,0		19
M21543-04-18	6	1/4"	-04	M 18x1,5	12	7,0	38,5	2,3	17,5		22
M21543-05-16	8	5/16"	-05	M 16x1,5	10	6,0	41,5	2,1	17,5		19
M21543-05-18	8	5/16"	-05	M 18x1,5	12	7,0	41,5	2,3	17,0		22
M21542-06-16	10	3/8"	-06	M 16x1,5	10	6,0	47,5	3,0	21,5		19
M21543-06-18	10	3/8"	-06	M 18x1,5	12	7,0	43,5	2,3	16,5		22
M21543-06-22	10	3/8"	-06	M 22x1,5	15	9,3	45,0	2,3	18,0		27
M21542-08-18	12	1/2"	-08	M 18x1,5	12	7,0	56,5	2,9	25,0		22
M21543-08-22	12	1/2"	-08	M 22x1,5	15	9,3	52,0	2,3	19,0		27
M21543-08-26	12	1/2"	-08	M 26x1,5	18	12,5	52,5	2,5	19,5		32
M21542-10-22	16	5/8"	-10	M 22x1,5	15	9,3	65,5	2,4	29,0		27
M21543-10-26	16	5/8"	-10	M 26x1,5	18	12,5	62,0	2,5	26,5		32
M21542-12-26	19	3/4"	-12	M 26x1,5	18	12,5	73,0	3,6	31,0		32
M21543-12-30	19	3/4"	-12	M 30x2	22	15,0	71,0	3,6	28,5		36
M21543-12-36	19	3/4"	-12	M 36x2	28	19,8	72,0	3,8	30,0		41
M21543-16-36	25	1"	-16	M 36x2	28	19,8	85,0	3,8	32,0		41
M21542-20-36	31	1.1/4"	-20	M 36x2	28	19,8	107,5	5,0	44,0		41
M21543-20-45	31	1.1/4"	-20	M 45x2	35	26,0	99,5	5,1	36,0		50
M21542-24-36	38	1.1/2"	-24	M 36x2	28	19,8	117,5	5,0	37,0		41
M21543-24-52	38	1.1/2"	-24	M 52x2	42	32,0	117,0	5,1	44,5		60