



M21592

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY
DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)



M21593

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY
DIN 20066 / ISO 12151-2 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size			T	mm	B	A	C	E
M21593-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	26,0	1,7	30,0		14
M21593-03-14	5	3/16"	- 03	M 14x1,5	8	4,0	29,0	1,7	31,5		17
M21592-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	28,5	2,2	32,5		17
M21593-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	29,5	1,7	31,5		17
M21593-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	29,5	2,1	32,0		19
M21593-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	29,5	2,3	33,0		22
M21592-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	31,0	1,7	33,0		17
M21593-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	32,0	2,1	32,5		19
M21593-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	32,0	2,3	32,5		22
M21593-05-22	8	5/16"	- 05	M 22x1,5	15	9,3	36,0	2,3	35,0		27
M21592-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	35,5	3,0	40,0		19
M21593-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	36,5	2,3	33,5		22
M21593-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	36,5	2,3	35,0		27
M21592-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	44,0	2,9	48,0		22
M21593-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	45,0	2,3	39,5		27
M21593-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	45,0	2,5	40,0		32
M21592-10-22	16	5/8"	- 10	M 22x1,5	15	9,3	53,5	3,0	57,5		27
M21593-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	51,5	2,5	53,0		32
M21593-10-30	16	5/8"	- 10	M 30x2	22	15,0	51,5	3,6	54,0		36
M21592-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	61,5	3,6	63,0		32
M21593-12-30	19	3/4"	- 12	M 30x2	22	15,0	61,5	3,6	59,0		36
M21593-12-36	19	3/4"	- 12	M 36x2	28	19,8	61,5	3,8	61,0		41
M21592-16-30	25	1"	- 16	M 30x2	22	15,0	79,5	3,6	80,5		36
M21593-16-36	25	1"	- 16	M 36x2	28	19,8	76,5	3,8	69,5		41
M21593-16-45	25	1"	- 16	M 45x2	35	26,0	79,0	5,1	72,0		50
M21592-20-36	31	1.1/4"	- 20	M 36x2	28	19,8	93,5	5,0	92,0		41
M21593-20-45	31	1.1/4"	- 20	M 45x2	35	26,0	93,5	5,1	81,0		50
M21592-24-36	38	1.1/2"	- 24	M 36x2	28	19,8	97,0	5,0	68,0		41
M21593-24-52	38	1.1/2"	- 24	M 52x2	42	32,0	107,5	5,1	98,0		60