




MULTIFIT TYPE



DIN STANDARD CONNECTIONS


M21642

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)



M21643

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm				
	DN	inch	Size			T	mm	B	A	C
M21643-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	38,5	3,5	17,5	17
M21643-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	36,0	3,4	15,0	19
M21643-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	37,5	3,0	16,5	22
M21643-05-18	8	5/16"	- 05	M 18x1,5	10	4,0	42,5	3,0	18,0	22
M21643-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	42,5	2,5	18,5	24
M21642-06-18	10	3/8"	- 06	M 18x1,5	10	4,0	49,0	3,9	23,0	22
M21643-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	45,0	2,5	18,0	24
M21643-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	46,5	3,0	19,5	27
M21642-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	57,5	2,5	25,5	27
M21643-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	52,5	3,0	20,0	30
M21643-10-30	16	5/8"	- 10	M 30x2	20	12,5	65,5	3,5	29,5	36
M21642-12-30	19	3/4"	- 12	M 30x2	20	12,5	76,5	2,2	34,0	36
M21643-12-36	19	3/4"	- 12	M 36x2	25	15,0	75,0	4,5	32,5	41
M21642-16-36	25	1"	- 16	M 36x2	25	15,0	98,0	1,7	43,5	41
M21643-16-42	25	1"	- 16	M 42x2	30	19,8	90,0	6,3	35,5	50
M21643-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	103,0	8,0	39,5	60