



### M22592

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)

### M22593

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M22593-03-04	5	3/16"	- 03	7/16" - 20	3,0	26,0	9,0	23,5		15
M22592-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,5	8,2	27,0		17
M22592-04-05	6	1/4"	- 04	1/2" - 20	4,0	28,5	9,2	27,5		17
M22593-04-06	6	1/4"	- 04	9/16" - 18	4,0	29,5	9,8	28,0		19
M22593-04-08	6	1/4"	- 04	3/4" - 16	7,0	29,3	11,0	30,5		22
M22592-05-05	8	5/16"	- 05	1/2" - 20	5,5	29,5	9,2	27,5		17
M22592-05-06	8	5/16"	- 05	9/16" - 18	7,0	31,0	9,2	28,5		19
M22592-06-05	10	3/8"	- 06	1/2" - 20	5,5	30,1	9,5	26,5		17
M22592-06-06	10	3/8"	- 06	9/16" - 18	7,0	35,5	9,2	32,5		19
M22593-06-08	10	3/8"	- 06	3/4" - 16	7,0	36,5	10,7	29,5		22
M22593-06-10	10	3/8"	- 06	7/8" - 14	9,3	36,5	12,4	31,5		27
M22592-08-06	12	1/2"	- 08	9/16" - 18	7,0	37,0	9,2	33,0		19
M22592-08-08	12	1/2"	- 08	3/4" - 16	9,3	44,0	10,2	41,0		22
M22593-08-10	12	1/2"	- 08	7/8" - 14	9,3	45,0	12,4	36,0		27
M22593-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	45,0	13,8	36,0		32
M22592-10-10	16	5/8"	- 10	7/8" - 14	12,5	53,5	12,3	52,5		27
M22593-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	51,5	13,8	50,0		32
M22592-12-10	19	3/4"	- 12	7/8" - 14	12,5	55,0	12,3	52,5		27
M22592-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	62,0	14,2	58,0		32
M22592-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	62,0	14,8	58,0		36
M22592-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	62,0	15,2	57,5		38
M22592-16-16	25	1"	- 16	1.5/16" - 12	19,8	77,0	15,2	67,0		38
M22592-16-20	25	1"	- 16	1.5/8" - 12	26,0	77,5	16,2	74,5		50
M22592-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	90,5	16,2	86,5		50
M22592-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	90,5	18,8	91,0		60
M22592-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	108,0	18,8	100,5		60
M22592-32-32	51	2"	- 32	2.1/2" - 12	44,0	142,0	24,0	137,0		75