




INTERLOCK PLUS TYPE

DIN STANDARD CONNECTIONS


M41642

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)



M41643

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm				
	DN	inch	Size			B	A	C	E	H ₂
M41643-10-30	16	5/8"	- 10	M 30x2	20	12,0	66,5	3,5	29,5	36
M41642-12-30	19	3/4"	- 12	M 30x2	20	12,5	79,2	3,2	34,8	36
M41643-12-36	19	3/4"	- 12	M 36x2	25	14,5	81,0	3,4	33,5	41
M41642-16-36	25	1"	- 16	M 36x2	25	16,0	103,0	4,1	45,5	41
M41643-16-42	25	1"	- 16	M 42x2	30	19,5	93,1	5,3	36,0	50
M41642-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	116,5	6,1	44,5	50
M41643-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	110,0	8,0	40,0	60