




INTERLOCK PLUS TYPE



DIN STANDARD CONNECTIONS


M41692

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)



M41693

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY
DIN 20066 / ISO 12151-2 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size			T	mm	B	A	C	E
M41693-10-30	16	5/8"	- 10	M 30x2	20	12,0	52,5	3,5	57,5		36
M41692-12-30	19	3/4"	- 12	M 30x2	25	12,5	63,8	3,2	68,5		36
M41693-12-36	19	3/4"	- 12	M 36x2	25	14,5	67,0	3,4	67,5		41
M41692-16-36	25	1"	- 16	M 36x2	25	16,0	81,7	4,1	89,0		41
M41693-16-42	25	1"	- 16	M 42x2	30	19,5	81,6	5,3	75,5		50
M41692-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	103,5	6,1	90,0		50
M41693-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	100,0	8,0	86,5		60