




INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS

M42411


ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H1	H2
M42411-10-10	16	5/8"	- 10	1" - 14	11,5	39,5	13,5		24	30
M42411-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	45,9	14,5		32	36
M42411-12-16	19	3/4"	- 12	1.7/16" - 12	19,0	46,5	15,0		36	41
M42411-16-12	25	1"	- 16	1.3/16" - 12	14,5	47,5	14,5		38	36
M42411-16-16	25	1"	- 16	1.7/16" - 12	19,5	48,5	15,0		41	41
M42411-16-20	25	1"	- 16	1.11/16" - 12	24,0	48,5	14,8		41	50
M42411-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	54,8	14,8		50	50
M42411-24-24	38	1.1/2"	- 24	2" - 12	31,0	57,8	15,8		60	60

M42412

ORFS FEMALE - SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H1	H2
M42412-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	37,0	14,0		32	36
M42412-16-16	25	1"	- 16	1.7/16" - 12	19,5	42,0	15,0		41	46
M42412-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	52,0	15,0		50	55
M42412-24-24	38	1.1/2"	- 24	2" - 12	31,0	55,0	15,0		60	60