

XTRAFLANGE


M68510

XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

BRIDA RECTA XTRAFLANGE (COMPATIBLE CON SAE J518 CODIGO 62 / ISO 6162-2)

XTRAFLANSCH GERADE (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			W.P.	WEIGHT
	DN	inch	Size		B	A	D		
M68510-16-16	25	1"	- 16	1"	20,0	69,5	47,7	560	0,6
M68510-20-20	31	1.1/4"	- 20	1.1/4"	24,0	88,0	54,4	560	1,0
M68510-20-24	31	1.1/4"	- 20	1.1/2"	30,5	100,0	63,7	560	1,3
M68510-24-24	38	1.1/2"	- 24	1.1/2"	30,5	102,0	63,7	560	1,4
M68510-32-32	51	2"	- 32	2"	41,0	129,0	79,6	450	2,7
M68510-40-40	63	2.1/2"	- 40	2.1/2"	51,5	149,0	99,2	350	4,4


M68590

90° XTRAFLANGE (SAE J518 CODE 62 AND ISO 6162-2 PORT COMPATIBLE)

BRIDA 90° XTRAFLANGE (COMPATIBLE CON SAE J518 CODIGO 62 / ISO 6162-2)

XTRAFLANSCH 90° BOGEN (J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				W.P.	WEIGHT
	DN	inch	Size		B	A	D	E		
M68590-16-16	25	1"	- 16	1"	20,0	84,2	47,7	90,0	560	0,8
M68590-20-20	31	1.1/4"	- 20	1.1/4"	24,0	107,0	54,4	120,0	560	1,5
M68590-24-24	38	1.1/2"	- 24	1.1/2"	30,5	122,2	63,7	140,0	560	2,2
M68590-32-32	51	2"	- 32	2"	41,0	147,5	79,6	180,0	450	4,3


M68540

45° XTRAFLANGE (SAE J518 CODE 62 AND ISO 6162-2 PORT COMPATIBLE)

BRIDA 45° XTRAFLANGE (COMPATIBLE CON SAE J518 CODIGO 62 / ISO 6162-2)

XTRAFLANSCH 45° BOGEN (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				W.P.	WEIGHT
	DN	inch	Size		B	A	D	E		
M68540-16-16	25	1"	- 16	1"	20,0	103,0	47,7	45,0	560	0,7
M68540-20-20	31	1.1/4"	- 20	1.1/4"	24,0	138,0	54,4	62,5	560	1,4
M68540-24-24	38	1.1/2"	- 24	1.1/2"	30,5	155,0	63,7	71,5	560	1,9
M68540-32-32	51	2"	- 32	2"	41,0	193,5	79,6	92,5	450	4,0