




OPNS TYPE

JIC STANDARD CONNECTIONS



OPNS12510

JIC MALE 37° CONE - SAE J516/J514

PART. REF.	HOSE BORE	THREAD	DIMENSIONS inch	
------------	-----------	--------	--------------------	--

	DN	inch	Size		B	A	C	F	H ₁	
OPNS12510-06-06	10	3/8"	- 06	9/16" - 18	0.28	2.32	0.55	1.17	0.67	
OPNS12510-06-08	10	3/8"	- 06	3/4" - 16	0.37	2.50	0.65	1.34	0.75	
OPNS12510-06-10	10	3/8"	- 06	7/8"-14	0.49	2.68	0.77	1.52	0.94	
OPNS12510-08-06	12	1/2"	- 08	9/16" -18	0.28	2.48	0.55	1.26	0.75	
OPNS12510-08-08	12	1/2"	- 08	3/4" - 16	0.37	2.58	0.65	1.35	0.75	
OPNS12510-08-10	12	1/2"	- 08	7/8" - 14	0.49	2.76	0.77	1.53	0.94	
OPNS12510-08-12	12	1/2"	- 08	1.1/16" - 12	0.59	2.91	0.87	1.69	1.06	
OPNS12510-10-10	16	5/8"	- 10	7/8" - 14	0.49	2.89	0.77	1.54	0.94	
OPNS12510-10-12	16	5/8"	- 10	1.1/16" - 12	0.59	3.03	0.87	1.68	1.06	
OPNS12510-12-10	19	3/4"	- 12	7/8" -14	0.49	3.07	0.77	1.63	1.06	
OPNS12510-12-12	19	3/4"	- 12	1.1/16" - 12	0.59	3.17	0.87	1.73	1.06	
OPNS12510-12-14	19	3/4"	- 12	1.3/16" - 12	0.63	3.19	0.89	1.75	1.26	
OPNS12510-12-16	19	3/4"	- 12	1.5/16" - 12	0.78	3.29	0.91	1.85	1.34	
OPNS12510-16-12	25	1"	- 16	1.1/16" - 12	0.59	3.66	0.87	1.76	1.26	
OPNS12510-16-16	25	1"	- 16	1.5/16" - 12	0.78	3.78	0.91	1.88	1.34	
OPNS12510-16-20	25	1"	- 16	1.5/8" - 12	1.02	3.98	0.96	2.08	1.65	
OPNS12510-20-20	31	1.1/4"	- 20	1.5/8" - 12	1.02	3.09	0.96	1.02	1.65	
OPNS12510-20-24	31	1.1/4"	- 20	1.7/8" - 12	1.26	3.33	1.08	1.26	1.97	
OPNS12510-24-24	38	1.1/2"	- 24	1.7/8" - 12	1.26	3.70	1.08	1.26	1.97	
OPNS12510-32-32	51	2"	- 32	2.1/2" - 12	1.65	4.25	1.34	1.65	2.56	