





OPNS TYPE

METRIC 24° O-RING STANDARD CONNECTIONS



OPNS21512

O-RING METRIC FEMALE 24° CONE L.T. - DIN 20066/3865
(THRUST-WIRE NUT)



OPNS21513

O-RING METRIC FEMALE 24° CONE L.T. - DIN 20066/3865
(SLIP-ON NUT)

PART. REF.	HOSE BORE	THREAD	PIPE	DIMENSIONS inch
------------	-----------	--------	------	--------------------

	DN	inch	Size		mm	B	A	C	F	H _i
OPNS21512-06-16	10	3/8"	- 06	M 16x1.5	10	0.24	2.07	0.12	0.91	0.75
OPNS21513-06-18	10	3/8"	- 06	M 18x1.5	12	0.28	2.03	0.09	0.88	0.87
OPNS21513-06-22	10	3/8"	- 06	M 22x1.5	15	0.37	2.14	0.09	0.98	1.06
OPNS21512-08-18	12	1/2"	- 08	M 18x1.5	12	0.28	2.37	0.11	1.14	0.87
OPNS21513-08-22	12	1/2"	- 08	M 22x1.5	15	0.37	2.22	0.09	1.00	1.06
OPNS21513-08-26	12	1/2"	- 08	M 26x1.5	18	0.49	2.26	0.10	1.03	1.26
OPNS21513-10-26	16	5/8"	- 10	M 26x1.5	18	0.49	2.37	0.10	1.02	1.26
OPNS21513-10-30	16	5/8"	- 10	M 30x2	22	0.59	2.69	0.14	1.34	1.42
OPNS21512-12-26	19	3/4"	- 12	M 26x1.5	18	0.49	2.66	0.14	1.22	1.26
OPNS21513-12-30	19	3/4"	- 12	M 30x2	22	0.59	2.55	0.14	1.11	1.42
OPNS21513-12-36	19	3/4"	- 12	M 36x2	28	0.79	2.54	0.15	1.11	1.61
OPNS21513-16-36	25	1"	- 16	M 36x2	28	0.78	3.06	0.15	1.16	1.61
OPNS21513-20-45	31	1.1/4"	- 20	M 45x2	35	1.02	3.36	0.20	1.30	1.97
OPNS21513-24-52	38	1.1/2"	- 24	M 52x2	42	1.26	3.74	0.20	1.29	2.36