


OPNS TYPE



METRIC 24° O-RING STANDARD CONNECTIONS


OPNS21612

O-RING METRIC FEMALE 24° CONE H.T.
DIN 20066/3865 (THRUST-WIRE NUT)



OPNS21613

O-RING METRIC FEMALE 24° CONE H.T.
DIN 20066/3865 (SLIP-ON NUT)



PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS inch					
	DN	inch			B	A	C	F	H ₂	
OPNS21613-06-20	10	3/8"	- 06	M 20x1.5	12	0.28	2.15	0.10	1.00	0.94
OPNS21613-06-22	10	3/8"	- 06	M 22x1.5	14	0.28	2.44	0.12	1.28	1.06
OPNS21613-08-24	12	1/2"	- 08	M 24x1.5	16	0.37	2.28	0.12	1.05	1.18
OPNS21613-10-30	16	5/8"	- 10	M 30x2	20	0.49	2.55	0.14	1.20	1.42
OPNS21612-12-30	19	3/4"	- 12	M 30x2	20	0.49	2.76	0.09	1.32	1.42
OPNS21613-12-36	19	3/4"	- 12	M 36x2	25	0.59	2.78	0.18	1.34	1.61
OPNS21612-16-36	25	1"	- 16	M 36x2	25	0.59	3.29	0.07	1.39	1.61
OPNS21613-16-42	25	1"	- 16	M 42x2	30	0.78	3.29	0.25	1.39	1.97
OPNS21613-20-52	31	1.1/4"	- 20	M 52x2	38	1.02	3.55	0.31	1.48	2.36
OPNS21613-24-52	38	1.1/2"	- 24	M 52x2	38	1.02	4.39	0.31	1.95	2.36