





# OPNS TYPE

## METRIC 24° O-RING STANDARD CONNECTIONS



### OPNS21692

90° O-RING METRIC FEMALE SWEPT ELBOW 24° CONE H.T.  
DIN 20066/3865 (THRUST-WIRE NUT)



### OPNS21693

90° O-RING METRIC FEMALE SWEPT ELBOW 24° CONE H.T.  
DIN 20066/3865 (SLIP-ON NUT)

PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS inch						
	DN	inch			B	A	C	E	F	H <sub>2</sub>	
OPNS21693-06-20	10	3/8"	- 06	M 20x1.5	12	0.28	2.59	0.10	1.38	1.44	0.94
OPNS21693-06-22	10	3/8"	- 06	M 22x1.5	14	0.28	2.59	0.12	1.46	1.44	1.06
OPNS21693-06-24	10	3/8"	- 06	M 24x1.5	16	0.37	2.60	0.12	1.42	1.44	1.18
OPNS21693-10-30	16	5/8"	- 10	M 30x2	20	0.49	3.38	0.14	2.26	2.03	1.42
OPNS21692-12-30	19	3/4"	- 12	M 30x2	20	0.49	3.86	0.09	2.66	2.42	1.42
OPNS21693-12-36	19	3/4"	- 12	M 36x2	25	0.59	3.86	0.18	2.54	2.42	1.61
OPNS21692-16-36	25	1"	- 16	M 36x2	25	0.59	5.03	0.07	3.39	3.13	1.61
OPNS21693-16-42	25	1"	- 16	M 42x2	30	0.78	5.01	0.25	2.93	3.11	1.97
OPNS21693-20-52	31	1.1/4"	- 20	M 52x2	38	1.02	5.75	0.31	3.37	3.68	2.36