





OPNS TYPE

ORFS STANDARD CONNECTIONS



OPNS22441

45° ORFS FEMALE - SAE J516/J1453
(CRIMPED-BACK NUT)



OPNS22443

45° ORFS FEMALE - SAE J516/J1453
(SLIP-ON NUT)

PART. REF.	HOSE BORE	THREAD	DIMENSIONS inch							
------------	-----------	--------	--------------------	--	--	--	--	--	--	--

	DN	inch	Size		B	A	C	E	F	H ₂
OPNS22443-06-06	10	3/8"	- 06	11/16" - 16	0.28	2.44	0.37	0.43	1.28	0.87
OPNS22443-06-08	10	3/8"	- 06	13/16" - 16	0.37	2.50	0.43	0.49	1.34	0.94
OPNS22441-08-06	12	1/2"	- 08	11/16" - 16	0.28	2.52	0.37	0.43	1.30	0.87
OPNS22443-08-08	12	1/2"	- 08	13/16" - 16	0.37	2.88	0.43	0.51	1.65	0.94
OPNS22443-08-10	12	1/2"	- 08	1" - 14	0.44	2.88	0.53	0.53	1.65	1.18
OPNS22443-08-12	12	1/2"	- 08	1.3/16" - 12	0.55	3.06	0.57	0.72	1.84	1.42
OPNS22443-10-10	16	5/8"	- 10	1" - 14	0.45	3.28	0.53	0.63	1.93	1.18
OPNS22443-10-12	16	5/8"	- 10	1.3/16" - 12	0.55	3.38	0.57	0.72	2.03	1.42
OPNS22441-12-10	19	3/4"	- 12	1" - 14	0.45	3.43	0.53	0.65	1.99	1.18
OPNS22443-12-12	19	3/4"	- 12	1.3/16" - 12	0.55	3.82	0.57	0.85	2.38	1.42
OPNS22443-12-16	19	3/4"	- 12	1.7/16" - 12	0.78	3.80	0.58	0.83	2.37	1.61
OPNS22443-16-16	25	1"	- 16	1.7/16" - 12	0.78	4.72	0.58	0.93	2.81	1.61
OPNS22443-16-20	25	1"	- 16	1.11/16" - 12	1.02	4.69	0.58	0.92	2.81	1.97
OPNS22443-20-20	31	1.1/4"	- 20	1.11/16" - 12	1.02	5.30	0.58	1.06	3.23	1.97
OPNS22443-24-24	38	1.1/2"	- 24	2" - 12	1.26	6.30	0.58	1.24	3.86	2.36