




OPNS TYPE



JIC STANDARD CONNECTIONS


OPNS22542

45° JIC FEMALE 37° CONE SEAT - SAE J516/J514
(THRUST-WIRE NUT)



OPNS22543

45° JIC FEMALE 37° CONE SEAT - SAE J516/J514
(SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS inch					
	DN	inch	Size		B	A	C	E	F	H ₂
OPNS22542-06-06	10	3/8"	- 06	9/16" - 18	0.28	2.81	0.36	0.65	1.65	0.75
OPNS22543-06-08	10	3/8"	- 06	3/4" - 16	0.28	2.77	0.42	0.55	1.61	0.87
OPNS22543-06-10	10	3/8"	- 06	7/8" - 14	0.37	2.83	0.49	0.61	1.67	1.06
OPNS22542-08-08	12	1/2"	- 08	3/4" - 16	0.37	3.27	0.40	0.79	2.05	0.87
OPNS22543-08-10	12	1/2"	- 08	7/8" - 14	0.37	3.17	0.49	0.67	1.95	1.06
OPNS22543-08-12	12	1/2"	- 08	1.1/16" - 12	0.49	3.19	0.54	0.67	1.97	1.26
OPNS22542-10-10	16	5/8"	- 10	7/8" - 14	0.49	3.79	0.48	1.00	2.44	1.06
OPNS22543-10-12	16	5/8"	- 10	1.1/16" - 12	0.49	3.71	0.54	0.94	2.36	1.26
OPNS22542-12-12	19	3/4"	- 12	1.1/16" - 12	0.59	4.19	0.56	1.08	2.76	1.26
OPNS22542-12-14	19	3/4"	- 12	1.3/16" - 12	0.59	4.15	0.58	1.08	2.72	1.42
OPNS22542-12-16	19	3/4"	- 12	1.5/16" - 12	0.78	4.19	0.60	1.08	2.76	1.50
OPNS22542-16-12	25	1"	- 16	1.1/16" - 12	0.59	4.75	0.56	1.08	2.85	1.26
OPNS22542-16-16	25	1"	- 16	1.5/16" - 12	0.78	5.28	0.60	1.27	3.39	1.50
OPNS22542-16-20	25	1"	- 16	1.5/8" - 12	1.02	5.44	0.64	1.42	3.54	1.97
OPNS22542-20-20	31	1.1/4"	- 20	1.5/8" - 12	1.02	6.14	0.64	1.63	4.07	1.97
OPNS22542-20-24	31	1.1/4"	- 20	1.7/8" - 12	1.26	6.26	0.74	1.75	4.19	2.36
OPNS22542-24-24	38	1.1/2"	- 24	1.7/8" - 12	1.26	7.13	0.74	1.83	4.69	2.36
OPNS22542-32-32	51	2"	- 32	2.1/2" - 12	1.73	9.02	0.94	2.68	6.42	2.95