





OPNS TYPE

JIC STANDARD CONNECTIONS



OPNS22592

90° JIC FEMALE 37° CONE SEAT - SAE J516/J514
(THRUST-WIRE NUT)



OPNS22593

90° JIC FEMALE 37° CONE SEAT - SAE J516/J514
(SLIP-ON NUT)

PART. REF.	HOSE BORE	THREAD	DIMENSIONS inch						
------------	-----------	--------	--------------------	--	--	--	--	--	--

	DN	inch	Size		B	A	C	E	F	H ₂
OPNS22592-06-05	10	3/8"	- 06	1/2" - 20	0.22	2.34	0.37	1.04	1.19	0.67
OPNS22592-06-06	10	3/8"	- 06	9/16" - 18	0.28	2.56	0.36	1.28	1.40	0.75
OPNS22593-06-08	10	3/8"	- 06	3/4" - 16	0.28	2.59	0.42	1.16	1.44	0.87
OPNS22593-06-10	10	3/8"	- 06	7/8"-14	0.37	2.60	0.49	1.24	1.44	1.06
OPNS22592-08-06	12	1/2"	- 08	9/16" - 18	0.28	2.68	0.36	1.30	1.46	0.75
OPNS22592-08-08	12	1/2"	- 08	3/4" - 16	0.37	2.96	0.40	1.61	1.73	0.87
OPNS22593-08-10	12	1/2"	- 08	7/8" - 14	0.37	3.00	0.49	1.42	1.77	1.06
OPNS22593-08-12	12	1/2"	- 08	1.1/16" - 12	0.49	2.99	0.54	1.42	1.77	1.26
OPNS22592-10-10	16	5/8"	- 10	7/8" - 14	0.49	3.46	0.48	2.07	2.11	1.06
OPNS22593-10-12	16	5/8"	- 10	1.1/16" - 12	0.49	3.38	0.54	1.97	2.03	1.26
OPNS22592-12-10	19	3/4"	- 12	7/8" - 14	0.49	3.60	0.48	2.07	2.17	1.06
OPNS22592-12-12	19	3/4"	- 12	1.1/16" - 12	0.59	3.88	0.56	2.28	2.44	1.26
OPNS22592-12-14	19	3/4"	- 12	1.3/16" - 12	0.59	3.88	0.58	2.28	2.44	1.42
OPNS22592-12-16	19	3/4"	- 12	1.5/16" - 12	0.78	3.88	0.60	2.26	2.44	1.50
OPNS22592-16-16	25	1"	- 16	1.5/16" - 12	0.78	4.73	0.60	2.64	3.03	1.50
OPNS22592-16-20	25	1"	- 16	1.5/8" - 12	1.02	4.94	0.64	2.93	3.04	1.97
OPNS22592-20-20	31	1.1/4"	- 20	1.5/8" - 12	1.02	5.63	0.64	3.41	3.56	1.97
OPNS22592-20-24	31	1.1/4"	- 20	1.7/8" - 12	1.26	5.63	0.74	3.58	3.56	2.36
OPNS22592-24-24	38	1.1/2"	- 24	1.7/8" - 12	1.26	6.69	0.74	3.96	4.25	2.36
OPNS22592-32-32	51	2"	- 32	2.1/2"-12	1.73	8.19	0.94	5.39	5.59	2.95