


OPS TYPE



ORFS STANDARD CONNECTIONS

OPS12410


ORFS RIGID MALE - SAE J516/J1453



PART. REF.	HOSE BORE			THREAD	DIMENSIONS inch				
	DN	inch	Size		B	A	C	F	H ₁
OPS12410-08-08	12	1/2"	- 08	13/16" - 16	0.37	2.43	0.50	1.20	0.87
OPS12410-12-12	19	3/4"	- 12	1.3/16" - 12	0.55	3.62	0.67	1.52	1.25
OPS12410-16-16	25	1"	- 16	1.7/16" - 12	0.75	3.93	0.69	1.60	1.50
OPS12410-20-20	31	1.1/4"	- 20	1.11/16" - 12	0.97	4.43	0.69	1.83	1.81
OPS12410-24-24	38	1.1/2"	- 24	2" - 12	1.19	4.59	0.69	1.91	2.17

OPS22411

ORFS FEMALE - SAE J516/J1453 (CRIMPED-BACK NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS inch					
	DN	inch	Size		B	A	C	F	H ₁	H ₂
OPS22411-06-06	10	3/8"	- 06	11/16" - 16	0.28	2.38	0.37	1.22	0.63	0.87
OPS22411-08-08	12	1/2"	- 08	13/16" - 16	0.37	2.64	0.43	1.41	1.75	0.94
OPS22411-10-10	16	5/8"	- 10	1" - 14	0.45	2.87	0.53	1.52	0.94	1.18
OPS22411-12-12	19	3/4"	- 12	1.3/16" - 12	0.55	3.85	0.57	1.76	1.10	1.42
OPS22411-12-16	19	3/4"	- 12	1.7/16" - 12	0.75	4.03	0.60	1.93	1.37	1.62
OPS22411-16-16	25	1"	- 16	1.7/16" - 12	0.75	4.27	0.60	1.94	1.37	1.62
OPS22411-20-20	31	1.1/4"	- 20	1.11/16" - 12	0.97	4.84	0.60	2.24	1.81	1.97
OPS22411-24-24	38	1.1/2"	- 24	2" - 12	1.19	5.00	0.58	2.32	1.97	2.36