




**MF<sup>TM</sup> 3000**

**OPS TYPE**

**SAE OR BOSS STANDARD CONNECTIONS**



**OPS13010**

**SAE O-RING RIGID MALE - SAE J516/J514**

| PART. REF.            | HOSE BORE |        |      | THREAD       | DIMENSIONS<br>inch |      |      |      |                |
|-----------------------|-----------|--------|------|--------------|--------------------|------|------|------|----------------|
|                       | DN        | inch   | Size |              | B                  | A    | C    | F    | H <sub>1</sub> |
| <b>OPS13010-06-06</b> | 10        | 3/8"   | - 06 | 9/16" - 18   | 0.28               | 2.17 | 0.39 | 1.01 | 0.67           |
| <b>OPS13010-08-08</b> | 12        | 1/2"   | - 08 | 3/4" - 16    | 0.37               | 2.36 | 0.44 | 1.14 | 0.87           |
| <b>OPS13010-08-10</b> | 12        | 1/2"   | - 08 | 7/8" - 14    | 0.49               | 2.48 | 0.50 | 1.26 | 1.00           |
| <b>OPS13010-12-12</b> | 19        | 3/4"   | - 12 | 1.1/16" - 12 | 0.55               | 3.63 | 0.59 | 1.54 | 1.25           |
| <b>OPS13010-12-16</b> | 19        | 3/4"   | - 12 | 1.5/16" - 12 | 0.78               | 3.65 | 0.59 | 1.56 | 1.50           |
| <b>OPS13010-16-16</b> | 25        | 1"     | - 16 | 1.5/16" - 12 | 0.75               | 3.89 | 0.59 | 1.56 | 1.50           |
| <b>OPS13010-20-20</b> | 31        | 1.1/4" | - 20 | 1.5/8" - 12  | 0.97               | 4.25 | 0.59 | 1.65 | 1.81           |