





OPS TYPE

BSP STANDARD CONNECTIONS



OPS20742


45° BSP FEMALE 60° CONE - BS5200 (THRUST-WIRE NUT)



OPS20743


45° BSP FEMALE 60° CONE - BS5200 (SLIP-ON NUT)

PART. REF.	HOSE BORE		THREAD	DIMENSIONS inch						
	DN	inch		Size	B	A	C	E	F	H ₂
OPS20743-06-06	10	3/8"	- 06	3/8" - 19	0.28	2.81	0.24	0.59	1.65	0.87
OPS20743-08-08	12	1/2"	- 08	1/2" - 14	0.37	3.19	0.25	0.67	1.95	1.06
OPS20742-12-12	19	3/4"	- 12	3/4" - 14	0.55	4.49	0.35	0.96	2.40	1.25
OPS20742-16-16	25	1"	- 16	1" - 11	0.75	5.09	0.42	1.11	2.77	1.62



OPS20792

90° BSP FEMALE 60° CONE - BS5200 (THRUST-WIRE NUT)



OPS20793

90° BSP FEMALE 60° CONE - BS5200 (SLIP-ON NUT)

PART. REF.	HOSE BORE		THREAD	DIMENSIONS inch						
	DN	inch		Size	B	A	C	E	F	H ₂
OPS20793-06-06	10	3/8"	- 06	3/8" - 19	0.28	2.60	0.24	1.24	1.44	0.87
OPS20793-08-08	12	1/2"	- 08	1/2" - 14	0.37	2.99	0.25	1.44	1.77	1.06
OPS20792-12-12	19	3/4"	- 12	3/4" - 14	0.55	4.13	0.35	1.94	2.03	1.25
OPS20792-16-16	25	1"	- 16	1" - 11	0.75	4.72	0.42	2.30	2.40	1.62