





# OPS TYPE

## METRIC 24° O-RING STANDARD CONNECTIONS



### OPS21692


90° O-RING METRIC FEMALE 24° CONE H.T.  
DIN 20066/3865 (THRUST-WIRE NUT)



### OPS21693


90° O-RING METRIC FEMALE 24° CONE H.T.  
DIN 20066/3865 (SLIP-ON NUT)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS inch					
	DN	inch	Size			mm	B	A	C	E	F
OPS21693-10-30	16	5/8"	- 10	M 30x2	20	0.49	3.39	0.14	2.26	2.03	1.42
OPS21692-12-36	19	3/4"	- 12	M 36x2	25	0.55	4.06	0.23	2.58	1.95	1.81
OPS21692-16-42	25	1"	- 16	M 42x2	30	0.75	4.72	0.34	2.61	2.40	1.97



### OPS21512

O-RING METRIC FEMALE 24° CONE L.T.  
DIN 20066/3865 (THRUST-WIRE NUT)



### OPS21513

O-RING METRIC FEMALE 24° CONE L.T.  
DIN 20066/3865 (SLIP-ON NUT)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS inch					
	DN	inch	Size			mm	B	A	C	F	H <sub>1</sub>
OPS21513-08-22	12	1/2"	- 08	M 22x1.5	15	0.37	2.49	0.09	1.27	-	1.06
OPS21513-10-26	16	5/8"	- 10	M 26x1.5	18	0.49	2.64	0.10	1.29	-	1.25
OPS21512-12-30	19	3/4"	- 12	M 30x2	22	0.55	3.71	0.17	1.49	1.26	1.42
OPS21512-16-36	25	1"	- 16	M 36x2	28	0.75	3.97	0.18	1.74	1.41	1.81