




OPK TYPE



BS STANDARD CONNECTIONS

OPK20512/OPK20513

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6

PART. REF.	HOSE BORE			Thread	DIMENSIONS mm						
	DN	Dash	inch		T	B	A	C	F	H2	
OPK20512-06-04	10	- 6	3/8"	1/4" - 19	4,1	47,5	4,2	18	19		
OPK20513-06-06	10	- 6	3/8"	3/8" - 19	7	49	6	19,5	22		
OPK20513-06-08	10	- 6	3/8"	1/2" - 14	9,3	49,5	6,3	20	27		
OPK20512-08-06	12	- 8	1/2"	3/8" - 19	7,1	52	6	21	22		
OPK20513-08-08	12	- 8	1/2"	1/2" - 14	9,3	51,5	6,3	20,5	27		
OPK20512-08-10	12	- 8	1/2"	5/8" - 14	12,1	53	10,2	22	28		
OPK20512-08-12	12	- 8	1/2"	3/4" - 14	15	56	9	24,5	32		
OPK20512-10-10	16	- 10	5/8"	5/8" - 14	12,5	56	10,2	21,5	28		
OPK20512-10-12	16	- 10	5/8"	3/4" - 14	15	57,5	9	23	32		
OPK20512-12-12	19	- 12	3/4"	3/4" - 14	15	61	9	24,5	32		
OPK20512-12-16	19	- 12	3/4"	1" - 11	19,8	62,5	10,5	26	38		
OPK20512-16-16	25	- 16	1"	1" - 11	19,8	75,5	10,5	27,5	38		

OPK20512: THRUST-WIRE NUT / OPK20513: SLIP-ON NUT