




**OPK TYPE**



**BS STANDARD CONNECTIONS**

**OPK20812/OPK20813**

**BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6**

PART. REF.	HOSE BORE			Thread	DIMENSIONS mm						
	DN	Dash	inch		T	B	A	C	F	H2	
OPK20812-06-04	10	- 6	3/8"	1/4" - 19	4,1	47,5	4,1	18	19		
OPK20813-06-06	10	- 6	3/8"	3/8" - 19	7	49	6	19,5	22		
OPK20813-08-08	12	- 8	1/2"	1/2" - 14	9,3	51,5	6,3	20,5	27		
OPK20812-10-10	16	- 10	5/8"	5/8" - 14	12,5	56,5	9,7	22	28		
OPK20812-12-12	19	- 12	3/4"	3/4" - 14	15	61,5	8,5	25	32		
OPK20812-16-16	25	- 16	1"	1" - 11	19,8	75,5	10,6	27,5	38		
OPK20812-16-20	25	- 16	1"	1.1/4" - 11	26,1	79	10,5	31	50		
OPK20812-20-20	31	- 20	1.1/4"	1.1/4" - 11	26	84	10,5	31,5	50		
OPK20812-20-24	31	- 20	1.1/4"	1.1/2" - 11	32,1	82	12,5	29,5	60		
OPK20812-24-24	38	- 24	1.1/2"	1.1/2" - 11	32	92,5	12,5	30,5	60		
OPK20812-24-32	38	- 24	1.1/2"	2"	42,1	92	16,1	30	70		
OPK20812-32-32	51	- 32	2"	2"	42	98	16,1	32	70		

OPK20812: THRUST-WIRE NUT / OPK20813: SLIP-ON NUT