





OPK TYPE



BS STANDARD CONNECTIONS

OPK20892/OPK20893

**90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO
12151-6**

PART. REF.	HOSE BORE			Thread	DIMENSIONS mm							
	DN	Dash	inch		T	B	A	C	E	F	H2	
OPK20892-06-04	10	- 6	3/8"	1/4" - 19		4,1	65	4,1	33	35,5	19	
OPK20893-06-06	10	- 6	3/8"	3/8" - 19		7	66	6	31,5	36,5	22	
OPK20893-08-08	12	- 8	1/2"	1/2" - 14		9,3	76	6,3	36,5	45	27	
OPK20892-10-10	16	- 10	5/8"	5/8" - 14		12,5	87,5	9,7	55	53	28	
OPK20892-12-12	19	- 12	3/4"	3/4" - 14		15	98	8,5	60	61,5	32	
OPK20892-16-16	25	- 16	1"	1" - 11		19,8	127,5	10,6	76	79,5	38	
OPK20892-16-20	25	- 16	1"	1.1/4" - 11		26,1	127,5	10,5	78,5	79,5	50	
OPK20892-20-20	31	- 20	1.1/4"	1.1/4" - 11		26	143	10,5	83,5	90,5	50	
OPK20892-20-24	31	- 20	1.1/4"	1.1/2" - 11		32,1	143	12,5	84,5	90,5	60	
OPK20892-24-24	38	- 24	1.1/2"	1.1/2" - 11		32	170	12,5	98,5	108	60	
OPK20892-32-32	51	- 32	2"	2" - 11		42	197	16,1	110,5	131	70	

OPK20892: THRUST-WIRE NUT / OPK20893: SLIP-ON NUT