




OPK TYPE



SAE STANDARD CONNECTIONS

OPK22592/OPK22593

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5

PART. REF.	HOSE BORE			Thread	T	DIMENSIONS mm						
	DN	Dash	inch			B	A	C	E	F	H2	
OPK22592-06-05'	10	-6	3/8"	1/2" - 20		5,5	59,5	9,1	26,5	30	17	
OPK22592-06-06'	10	-6	3/8"	9/16" - 18		7	65	9,2	32,5	35,5	19	
OPK22593-06-08'	10	-6	3/8"	3/4" - 16		7	66	10,1	29,5	36,5	22	
OPK22593-06-10'	10	-6	3/8"	7/8" - 14		9,3	66	12,4	31,5	36,5	27	
OPK22592-08-06'	12	-8	1/2"	9/16" - 18		7	68	9,2	33	37	19	
OPK22592-08-08'	12	-8	1/2"	3/4" - 16		9,3	75,5	10,2	41	44	22	
OPK22593-08-10'	12	-8	1/2"	7/8" - 14		9,3	76	12,4	36	45	27	
OPK22593-08-12	12	-8	1/2"	1.1/16" - 12		12,5	76	14,1	36	45	32	
OPK22592-10-10	16	-10	5/8"	7/8" - 14		12,5	88	12,3	52,5	53,5	27	
OPK22593-10-12	16	-10	5/8"	1.1/16" - 12		12,5	86	14,1	50	51,5	32	
OPK22592-12-10	19	-12	3/4"	7/8" - 14		12,5	91,5	12,3	52,5	55	27	
OPK22592-12-12	19	-12	3/4"	1.1/16" - 12		15	98	14,2	58	62	32	
OPK22592-12-14	19	-12	3/4"	1.3/16" - 12		15	99	14,3	58	63	36	
OPK22592-12-16	19	-12	3/4"	1.5/16" - 12		19,8	99	15	57,5	63	38	
OPK22592-16-16	25	-16	1"	1.5/16" - 12		19,8	124	15	68,5	76	38	
OPK22592-16-20	25	-16	1"	1.5/8" - 12		26	125,5	16,2	74,5	77,5	50	
OPK22592-20-20	31	-20	1.1/4"	1.5/8" - 12		26	143	16,2	86,5	90,5	50	
OPK22592-20-24	31	-20	1.1/4"	1.7/8" - 12		32	143	18,8	90,5	90,5	60	
OPK22592-24-24	38	-24	1.1/2"	1.7/8" - 12		32	170	18,8	100,5	108	60	
OPK22592-32-32	51	-32	2"	2.1/2" - 12		44	208	24	137	142	75	

OPK22592: THRUST-WIRE NUT / OPK22593: SLIP-ON NUT