




OPK TYPE



SAE STANDARD CONNECTIONS

OPK22711/OPK22711KR

**JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO
12151-5**

PART. REF.	HOSE BORE			Thread		DIMENSIONS mm						
	DN	Dash	inch			T	B	A	C	F	H1	H2
OPK22711-06-06KR	10	- 6	3/8"	9/16" - 18		7	51,5	9,5	22	17	17	
OPK22711-06-08KR	10	- 6	3/8"	3/4" - 16		9,3	56	10,7	26,5	19	22	
OPK22711-08-08KR	12	- 8	1/2"	3/4" - 16		9,3	58	10,7	27	19	22	
OPK22711-08-10KR	12	- 8	1/2"	7/8" - 14		9,3	60,5	12,5	29,5	22	25	
OPK22711-08-12KR	12	- 8	1/2"	1.1/16" - 12		15	60	14,1	28,5	27	32	
OPK22711-10-08KR	16	- 10	5/8"	3/4" - 16		9,3	62,5	10,7	28,5	22	22	
OPK22711-10-10KR	16	- 10	5/8"	7/8" - 14		12,5	64	12,5	29,5	22	25	
OPK22711-12-08KR	19	- 12	3/4"	3/4" - 16		9,3	66	10,7	29,5	27	22	
OPK22711-12-10KR	19	- 12	3/4"	7/8" - 14		12,5	67	12,5	30,5	27	25	
OPK22711-12-12KR	19	- 12	3/4"	1.1/16" - 12		15	66,5	14,1	30	27	32	
OPK22711-12-16	19	- 12	3/4"	1.5/16" - 12		19,8	71	15,3	34,5	32	38	
OPK22711-16-12KR	25	- 16	1"	1.1/16" - 12		15	80,5	14,1	32,5	32	32	
OPK22711-16-16	25	- 16	1"	1.5/16" - 12		19,8	83,5	15,3	35,5	32	38	

KR:CRIMPED-BACK KOMPACT ROBUST NUT